

رؤية
2030
المملكة العربية السعودية
KINGDOM OF SAUDI ARABIA



EV Safety
Charger Unit

Quality Approvals for Various Products and Services





Charger Unit

Cabinet Details

- Dimension: 400 x 400 x 1800

LED Strip Light with IP65

Heavy Duty Door Enclosure

Material Specifications

- Mild Steel
- Stainless Steel
- Mild Steel with Intecel
- Aluminium
- Aluminium with Intecel

EV Charger Details

- Power adjustable by a switch or APP
- Up to 32A, 400V maximum power of 22kw 3ph
- For business or home use
- Capable of charging at full power between -20°~ +55°C
- IP65

Charging Mode: Smart Charging

Input/Output power rating and current: 3 Phase up to 22 kW / 32A

Input / Output Voltage: 400V \pm 20%, 3 Phase, 50 Hz

Network Type: TT, TN

Internal RCD: AC 30mA, DC 6mA

Protection: Overcurrent, Overvoltage, Undervoltage, Integrated Surge Protection

Card Reader: ISO 15693, ISO 14443

Power Measurement Accuracy: \pm 1.0% from 1% to full scale

Fire Extinguisher Details

- 4Kg, Special Fire Extinguisher for Electric Vehicle



Car Fire Blanket

- **Composition:**
Fiberglass with silicone coat

Density: 480 g/m2

Reaction to fire classification: A2-s1

Scan the QR Code for more information

