



HAWK 2

MEDIUM SIZE FIRE FIGHTING VEHICLE

The SFFECO Hawk Series 2 stands as the most advanced and highly sought-after model in the field of fire fighting vehicles, designed to meet the intense demands of both municipal and industrial fire emergencies. This versatile and robust firefighting apparatus is engineered to handle the most challenging fire scenarios, offering an exceptional capacity to carry larger quantities of water and foam. This allows for extended firefighting operations without the need for frequent resupply. Whether it's tackling hazardous industrial fires or providing swift response in urban environments, the SFFECO Hawk Series 2 is built to deliver unparalleled performance and reliability, becoming an indispensable asset for modern firefighting operations.

SFFECO Hawk Series 2 is commonly built on IVECO/ISUZU Chassis



HAWK 2

MEDIUM SIZE FIRE FIGHTING VEHICLE

Body Work:

The body structure is so designed to allow the most rugged operation condition. Compartment rooms are readily available for carrying necessary tools and equipment. Holders are provided so that equipment will remain in place under running conditions and permit quick removal for use. Service openings and access doors are also provided at important areas where inspection and maintenance work is very vital.

Water Tank:

The tank is made of corrosion proof 304 type stainless steel sheet 3mm wall thickness and 3 mm base thickness.

Water tank capacity is 3000L - 5000L

Foam Tank:

The tank is made of corrosion proof stainless steel sheet 316L, 3mm wall thickness and 3mm base thickness. The tank is designed to store all known foam compounds in all running condition.

Foam tank capacity is 300L - 500L

Features:

Rapid Intervention Vehicle
Built over IVECO Chassis
Single Cabin
Water Tank Capacity is 3000L - 5000L
Foam Tank Capacity is 300L - 500L

Fire Pump: Tohatsu VC52AS / VC72AS

1300 L/Min at 0.6 MPa (6 bar)
1000 L/Min at 0.8 MPa (8 bar)
600 L/Min at 1.0 MPa (10 bar)

Monitor:

Model: SF-26A
Dual Gear Manual Operation, 2½" two way waterway

Monitor Nozzle:

Model : SL-19MS
Flow: 400 Lpm @ 7 Bar
Shooting Range: 38 Mtr. @ 45 Deg.

Other Accessories:

Hose Holder
Synthetic Hose
Hose Nozzle
Hose Reel
Hydrant Wrench
Hose Spanner for Fire Hose & Suction Hose
Powder Extinguisher & CO2 Extinguisher
Aluminum Two Section Ladder
Suction hose and Check Valve with Strainer
Light bar

Factory - Riyadh

2nd Industrial Area, Al-Kharj Road, Riyadh, KSA
P.O. Box: 4441, Riyadh 14334
Tel : +966 11 2650070, Fax: +966 11 2652190
E-mail: riyyadh@sffeco.com.sa

SFFECO Global - Dubai

P.O. Box: 261318, JAFZA South, Dubai U.A.E.
Tel : +971 4 880 9890, Fax: +971 4 880 9822
E-mail: sales@sffecoglobal.com

Jeddah Branch

P.O. Box: 16769, Jeddah - 21474, KSA
Tel : +966 12 670 6009, Fax: +966 12 676 0307
E-mail: jeddah@sffeco.com.sa

Dammam Branch

P.O. Box: 7162, Dammam - 31462, KSA
Tel : +966 13 8351961, Fax: +966 13 8351968
E-mail: dammam@sffeco.com.sa

Madinah Branch

Tel : 0148660959, 0148283256, Fax: 0148660969
E-mail: madinah@sffeco.com.sa



www.SFFECO.com

