



# **HAWK 3**

## **MEDIUM SIZE FIRE FIGHTING VEHICLE**

The SFFECO Hawk Series 3 is our most advanced and highly efficient fire truck, specifically designed to meet the demands of both municipal and industrial firefighting operations. Built for maximum performance, it claims an enhanced capacity to carry larger volumes of water and foam, ensuring longer operational durations without the need for frequent refills. In addition to its impressive fluid capacity, the SFFECO Hawk Series 3 comes equipped with a full array of specialized firefighting tools and equipment, providing fire crews with everything needed to tackle diverse fire scenarios. Whether combating large-scale industrial blazes or responding swiftly to urban fires, the Hawk Series 3 offers unmatched reliability and operational efficiency, making it the ultimate choice for demanding firefighting challenges.

SFFECO Hawk Series 3 is commonly built on IVECO Chassis



# HAWK 3

## MEDIUM SIZE FIRE FIGHTING VEHICLE

### Body Work:

The body structure is so designed to allow the most rugged operation condition. Compartment rooms are readily available for carrying necessary tools and equipment. Holders are provided so that equipment will remain in place under running conditions and permit quick removal for use. Service openings and access doors are also provided at important areas where inspection and maintenance work is very vital.

### Water Tank:

The tank is made of corrosion proof 304 type stainless steel sheet 3mm wall thickness and 3 mm base thickness.

Water tank capacity is 5500L - 7500L

### Foam Tank:

The tank is made of corrosion proof stainless steel sheet 316L, 3mm wall thickness and 3mm base thickness. The tank is designed to store all known foam compounds in all running condition.

Foam tank capacity is 550L - 750L

### Features:

Rapid Intervention Vehicle  
Built over IVECO Chassis  
Single Cabin  
Water Tank Capacity is 5500L - 7500L  
Foam Tank Capacity is 550L - 750L

### Fire Pump: DARLEY HGE 37V - Medium Pressure

550 gpm (2081 L/M) @ 30 psi (2.0 bar)  
300 gpm (1135 L/M) @ 105 psi (7.2 bar)  
100 gpm (378 L/M) @ 195 psi (13.4 bar)

### Monitor:

Model: SF-26A  
Dual Gear Manual Operation, 2½" two way waterway

### Monitor Nozzle:

Model : SL-19MS  
Flow: 400 Lpm @ 7 Bar  
Shooting Range: 38 Mtr. @ 45 Deg.

### Other Accessories:

Hose Holder  
Synthetic Hose  
Hose Nozzle  
Hose Reel  
Hydrant Wrench  
Hose Spanner for Fire Hose & Suction Hose  
Powder Extinguisher & CO2 Extinguisher  
Aluminum Two Section Ladder  
Suction hose and Check Valve with Strainer  
Light bar

### Factory - Riyadh

2nd Industrial Area, Al-Kharj Road, Riyadh, KSA  
P.O. Box: 4441, Riyadh 14334  
Tel : +966 11 2650070, Fax: +966 11 2652190  
E-mail: riyyadh@sffeco.com.sa

### SFFECO Global - Dubai

P.O. Box: 261318, JAFZA South, Dubai U.A.E.  
Tel: +971 4 880 9890, Fax: +971 4 880 9822  
E-mail: sales@sffecoglobal.com

### Jeddah Branch

P.O. Box: 16769, Jeddah - 21474, KSA  
Tel : +966 12 670 6009, Fax: +966 12 676 0307  
E-mail: jeddah@sffeco.com.sa

### Dammam Branch

P.O. Box: 7162, Dammam - 31462, KSA  
Tel : +966 13 8351961, Fax: +966 13 8351968  
E-mail: dammam@sffeco.com.sa

### Madinah Branch

Tel : 0148660959, 0148283256, Fax: 0148660969  
E-mail: madinah@sffeco.com.sa



www.SFFECO.com

