



HAWK 4

LONG FIRE FIGHTING VEHICLE

The SFFECO Hawk Series 4 is a powerful firefighting vehicle designed for high-risk environments, such as oil refineries and chemical plants, where highly flammable materials are present. It features advanced technology, including high-capacity pumps and foam systems that are effective in handling oil and chemical fires.

The vehicle's rugged build allows it to operate in tough conditions and reach hard-to-access areas, while its foam systems help smother flames and prevent re-ignition. The Hawk Series 4 is built with firefighter safety in mind, offering protection and specialized tools for efficient firefighting in dangerous industrial operations.

SFFECO Hawk Series 4 is commonly built on IVECO/Mercedes Chassis





HAWK 4

LONG FIRE FIGHTING VEHICLE

Body Work:

The body structure is so designed to allow the most rugged operation condition. Compartment rooms are readily available for carrying necessary tools and equipment. Holders are provided so that equipment will remain in place under running conditions and permit quick removal for use. Service openings and access doors are also provided at important areas where inspection and maintenance work is very vital.

Water Tank:

The tank is made of corrosion proof 304 type stainless steel sheet 3mm wall thickness and 3 mm base thickness.

Water tank capacity is 8,000L - 15000L

Foam Tank:

The tank is made of corrosion proof stainless steel sheet 316L, 3mm wall thickness and 3mm base thickness. The tank is designed to store all known foam compounds in all running condition.

Foam tank capacity is 800L - 1500L

Features:

Rapid Intervention Vehicle
Built over IVECO Chassis
Single Cabin
Water Tank Capacity is 8000L - 15000L
Foam Tank Capacity is 800L - 1500L

Fire Pump: LSPH 1000 / LSRH 1000

1000 gpm (3785 L/M) @ 150 psi (10.3 bar)
700 gpm (2646 L/M) @ 200 psi (13.8 bar)
500 gpm (1893 L/M) @ 250 psi (17.2 bar)

Monitor:

Model: SL-19GM-L
NH 2-1/2", 3", Flow Rate: 350, 500 / 750, 1000 GPM @ 7 barg.

Monitor Nozzle:

Model: SL-19MS
Flow: 400 Lpm @ 7 Bar
Shooting Range: 38 Mtr. @ 45 Deg.

Other Accessories:

Hose Holder
Synthetic Hose
Hose Nozzle
Hose Reel
Hydrant Wrench
Hose Spanner for Fire Hose & Suction Hose
Powder Extinguisher & CO2 Extinguisher
Aluminum Two Section Ladder
Suction hose and Check Valve with Strainer
Light bar

Factory - Riyadh

2nd Industrial Area, Al-Kharj Road, Riyadh, KSA
P.O. Box: 4441, Riyadh 14334
Tel: +966 11 2650070, Fax: +966 11 2652190
E-mail: riyadh@sffeco.com.sa

SFFECO Global - Dubai

P.O. Box: 261318, JAFZA South, Dubai U.A.E.
Tel: +971 4 880 9890, Fax: +971 4 880 9822
E-mail: sales@sffecoglobal.com

Jeddah Branch

P.O. Box: 16769, Jeddah - 21474, KSA
Tel: +966 12 670 6009, Fax: +966 12 676 0307
E-mail: jeddah@sffeco.com.sa

Dammam Branch

P.O. Box: 7162, Dammam - 31462, KSA
Tel: +966 13 8351961, Fax: +966 13 8351968
E-mail: dammam@sffeco.com.sa

Madinah Branch

Tel: 0148660959, 0148283256, Fax: 0148660969
E-mail: madinah@sffeco.com.sa



www.SFFECO.com

