

Mobile CO2



Note:

Model TC10, TC25, TC30, TCB100 and TC50 are SASO Approved

SFFECO Mobile carbon dioxide fire extinguishers are known for its high reliable performance. The cylinders of CO2 fire extinguishers are seamless and are extruded from high grade Chrome Molybdenum Steel or Manganese or Carbon Steel.

Suitable to use on Class B and Electrical fires.

The CO2 extinguisher is especially effective on electrical fires because, being a gas; it does not leave any residues which might further harm the damaged equipment.

Technical Specifications:

- ❖ Extinguishing Agent : CO2
- ❖ Test Pressure : 250 Bar
- ❖ Coating : Electrostatic Polyester Powder
- ❖ Storage Temperature : -20°C to +60°C

Class of Fire:



Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.



Fires on electrical plants.

Model	TC10	TC25	TC30	TCB100
Capacity	10 Kg	25 Kg	30 Kg	45.5 Kg
Total Weight	38 Kg	96 Kg	102 Kg	124.6 Kg
Total Height (mm)	1025	1420	1420	1650
Total Width (mm)	440	590	590	590
Total Depth (mm)	940	1310	1310	1500
Hose Length (mm)	3500	3500	3500	6000
Maximum Effective Range (m)	4	6	6	6
Duration of Discharge (Sec)	40-50	75-80	90-94	110-120