

Discharge Nozzle-Dome Type

Size: 1/2"

P/N: SFR-CDES-DC-26



| Discharge Nozzle-Dome Type | P/N: SFR-CDES-DC-26 |
|----------------------------|---------------------|
| Standard | UL 2127, NFPA 12 |
| Material | Stainless Steel |
| Threads | 1/2" BSP (F) |
| Temperature Ratings | -18°C to +54.4° C |
| Orifice Size | As per requirement |

Discharge Nozzle – Open Type

Size: 1/2"

P/N: SFR-CDES-DC-27



| Discharge Nozzle-Open Type | P/N: SFR-CDES-DC-27 |
|----------------------------|---------------------|
| Standard | UL 2127, NFPA 12 |
| Material | Stainless Steel |
| Threads | 1/2" BSP (M) |
| Temperature Ratings | -18°C to +54.4° C |
| Orifice Size | As per requirement |

Discharge Nozzle-Reset Type

Size: 1/2"

P/N: SFR-CDES-DC-28



| Discharge Nozzle-Reset Type | P/N: SFR-CDES-DC-28 |
|-----------------------------|--------------------------------|
| Standard | UL 2127, NFPA 12 |
| Material | Stainless Steel |
| Threads | 1/2" BSP (M) |
| Temperature Ratings | -18°C to +54.4° C |
| Orifice Size | As per requirement (Room Size) |